



## Fodenn Electronic Technology Co.,Ltd

Add: 3rd floor, Building B, Runchang industrial park, Zhonghao 2 road,  
Bantian street, Longgang district, Shenzhen

Tel: 0755-86329789 Fax: 0755-83689236 Email: oversea1@fodenn.com

---

### IPC-AC200 Industrial Computer



#### Features

- Intel low-power embedded industrial host
- Support DDR3L notebook memory
- VGA+HDMI supports dual screen synchronization/asynchrony
- Support 4 COM
- Support 4 USB 2.0+1 USB3.0
- Onboard 1 MSATA
- Onboard 1 MINI PCIE

#### Application

Industrial automation, Rail transit, Financial equipment, Medical and social security, MINIBOX, Interactive application, All-in-one computer, etc.



## Fodenn Electronic Technology Co.,Ltd

Add: 3rd floor, Building B, Runchang industrial park, Zhonghao 2 road,  
Bantian street, Longgang district, Shenzhen

Tel: 0755-86329789 Fax: 0755-83689236 Email: oversea1@fodenn.com

### Specifications

<b>Product Model</b>	<b>IPC-AC200</b>
<b>CPU</b>	Intel J1900 CPU
<b>System Memory</b>	1*DDR3LSODMM supports 4GB, Maximum support 8GB
<b>Display Chip</b>	Intel® HD Graphics
<b>LAN Function</b>	2*Intel WG210AT Gigabit LAN, support Wake-on-LAN function
<b>Display Port</b>	VGA1, HMDI, LVDS (DEFAULT) /EDP
<b>Sound Card</b>	LINE OUT *1 MIC IN *1 Support power amplifier, 2 way 4 ohm 3W speaker
<b>Expansion Plug</b>	2*MINIPCI-E1, 1 support WIFI, 1 support 4G
<b>Storage</b>	1*SATA1 Interface 7 (optional), a hard disk power supply interface 1*MSATA
<b>Function</b>	One 7+5 notebook hard drive interface (DEFAULT)
<b>USB Port</b>	6 USB2.0, the panel supports 4 USB2.0, the other 2 are 1 set of 2.0 headers 1 USB3.0 (compatible with USB2.0)
<b>PS/2</b>	N/A
<b>Serial Port</b>	Supports 6 RS232, COM1 and COM2 support RS422 and RS485 at the same time, not support power supply. COM1/2/3/4 uses DB9, not support power supply COM5 and COM6 are HEADER port
<b>Parallel Port</b>	N/A
<b>GPIO</b>	8 Independent Digital GPIO, COM4 optional
<b>Fan Interface</b>	CPU_FAN1, SYS_FAN1
<b>Button</b>	Power button and reset button
<b>Indicator Light</b>	Power light, hard disk light
<b>Power Supply</b>	12 DC, DC-025M with threaded lock
<b>Dimensions</b>	180MM* 121.2MM* 30MM