

IPC-HC1210 Industrial Computer



Features

- Intel low-power embedded industrial computer
- Support DDR3L notebook memory
- VGA+HDMI supports dual screen synchronization/asynchrony
- Support 10 COM ports
- Support 7USB2.0 1*USB3.0
- 2 Gigabit network port
- Support WIFI or 4G

Application

Industrial Automation, Rail Transit, Financial Equipment, Medical and Social Security, MINIBOX, Interactive Application, All-in-one computer, etc.



Fodenn Electronic Technology Co.,Ltd

Add: 3rd floor, Building B, Runchang industrial park, Zhonghao 2 road,
Bantian street, Longgang district, Shenzhen

Tel: 0755-86329789 Fax: 0755-83689236 Email: oversea1@fodenn.com

Specifications

| | |
|---|---|
| CPU | Intel® J1900 4-core 2.0Hz CPU |
| System Memory | 1*SODM DDR3L, up to 4GB |
| Storage | L*MSATA |
| Display Chip | Intel® HD Graphics |
| Display Port | Provides VGA+HDMI dual display, supports synchronous/asynchronous |
| Network RJ-45 | onboard Realtek 8111E Gigabit dual network port |
| WIFI | Support |
| 4G Network | Support |
| Sound Card | Realtek ALC662 |
| COM | 10 COM, COM1 COM2 supports 5V/12V live COM2 supports RS422 and RS485 functions |
| Front I/O | One power switch One power indicator One hard disk indicator One antenna port+1*PS/2 |
| Rear I/O | DC 12V power + VGA + HDMI 8*USB + dual network port Audio output |
| Physical parameters | |
| Dimensions | 243MM*69MM*146MM |
| Weight | 2.0KG |
| Application | Operating Temperature 0~50°C |
| Environment | Storage Temperature -40~75°C |
| Compatible operating system (standard without operating system) WINDOWS7, WINDOWS8, WINDOWS10, LINUX. | |